SOLUTIONS FOR THE TRADE











ANGLE STOP 15MM FEMALE G 1/2, G 1/2

79241.02







ANGLE STOP 15MM FEMALE

G 1/2, G 3/8 79246.02



WASHING MACHINE TAP 15MM FEMALE

WITH COLD AND HOT INDICATORS G 1/2, G 3/4 79242.02





COMBI VALVE 15MM

G 1/2, G1/2, G 3/4 79247.02





ANGLE STOP MALE AND 300MM FLEXI **HOSE 15MM**

G 1/2, G 1/2 WITH COLD AND HOT INDICATORS 79248 02





ANGLE STOP FEMALE AND 300MM FLEXI HOSE 15MM

G 1/2, G 1/2 79249.02





FLEXI HOSE 300MM (20BAR-2000KPA)



2 WAY SHUT OFF VALVE 15MM MALE

G 1/2, G 1/2, G 1/2 79244.02



MINI BALL VALVE 15MM MALE AND FEMALE

G 1/2, G/12 79243.02

FEATURES

- For use with cold and hot water up to 95°C
- Maximum working pressure 20bar
- O-rings made of NBR and POM
- Threads ISO228
- High-quality chrome plating
- European Brass CW617 is more resistant (more copper in composition) avoiding any leaking risk. (79240.02/79249.02)
- · Stainless steel rosettes

Quarter turn Twin system featuring one handle that has four independent positions to control two independent outlets.













MADE IN SPAIN



FIFTEEN YEAR GUARANTEE



QUARTER TURN SYSTEM APPLIES TO 79244.02



INTERNAL CHECK VALVES INCLUDED APPLIES TO 79241.02, 79242.02 & 79249.02



EUROPEAN BRASS CW617

