Page 3 of 4

ELEMENTi

Ion/Neo bath Column W/Hand Piece

GUARANTEES

Robertson offers 5 years guarantee on ceramic cartridges and other material excluding washers, o-rings and other perishable components.

Where the product fails within the warranty period we offer a free replacement or replacement part (or nearest equivalent) or to repair the failed product.

This guarantee is transferable – it applies to the product not the purchaser provided proof or purchase details are passed on to the new owner. This guarantee does not affect your statutory rights.

Products must be installed, used and cared for in line with product guidelines, our fixing instructions and building regulations.

In addition to specific guarantees provided, all products imported and sold by Robertson are, to the extent applicable and guaranteed in accordance with the durability clauses of the New Zealand Building regulations and the Consumer Guarantees Act.

Some product warranties may be effected by misuse or local conditions eg. Adverse cleaning products. The warranty and guarantees given by Robertson may be void where repair work is carried out by persons not specifically authorised to carry out such work by Robertson.

The above guarantees apply only to products imported and sold by Robertson. These guarantees do not cover products sold by Robertson under any other agency company or brand name.

IMPORTANT:

Products must be inspected prior to installation.

Please ensure that all products purchased from Robertson are inspected prior to installation. Any suspected defect in a product must be notified to Robertson as soon as possible after discovery. Should any defects be found do not install. Return the product to the point of purchase for a replacement. If a product is installed despite a fault having been identified prior to installation, Robertson will not accept any liability for the cost of the labour to remove and install any replacement product.

Warranty Conditions

This warranty will apply only under all of the following conditions:

- The item has been installed as per the conditions of the recommend use
- Failure is due to a fault in the manufacture of the product

Page 4 of 4

- Proof of purchase (including the date of purchase)
 is provided
- The installation of the product is in accordance with the instructions provided

This warranty does not cover products purchased as an ex-display without being fully checked and tested for sale by the manufacturer.

This warranty does not include faults caused by:

- Unsuitable or improper use.
- Incorrect installation or installation not in accordance with the instructions provided.
- Normal wear and tear.
- Inadequate or complete lack of maintenance.
- Chemical, electrochemical or electrical influences.
- Harsh detergents or abrasive cleaners used on product finishes.

CARE AND MAINTAINANCE


Where your tapware remains dry in use, a soft cloth should be used to remove surface dust. Alternatively, a wipe over with warm soapy water is all that is required to maintain the finish in perfect condition for a lifetime of use, the surface duration depends on the altention and care by which they are handled by users. Deterioration of surface finishes due to use of cleaning agents containing acids or abrasive substances will not be covered under warrant.

CLAIM PROCEDURE

For all warranty queries customers are to contact the store where the product was purchased. These details can be found on your purchase invoice.

ELEMENTi Page 1 of 4

Ion/Neo bath Column W/Hand Piece



Recommended use	Domestic and Hotel
Colour availability	Chrome,Gun Metal,Black,Brushed Nickel,Brushed Brass
Pressure rating	Mains Pressure-Equal
	Maximum operating pressure 500 KPa.
	Minimum operating pressure 150 Kpa.
Temperature rating	Maximum continuous working temperature 70°
Suitable Hot Water Units	
	Continuous Flow: Yes
	Gravity Feed: Not recommended
WELS	Mains Pressure-Equal
	Stars: 3
	Flow rate: 9 L/Min



ELEMENTI

Ion/Neo bath Column W/Hand Piece

INSTALLATION

Important Note

Mixer must be installed to the requirements of AZ/NZS 3500. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantiling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

- Please ensure pipework is clear of debris by flushing the lines prior to commencing the installation of the mixer.
- Mains Pressure Equal recommend connection to hot/cold isolation valves, test operation.


TWISTING OR STRETCHING OF FLEXIBLE HOSES DURING INSTALLATION MAY RESULT IN FAILURE AND VOID WARRANTY ISOLATE MIXER BEFORE HYDROSTATIC TEST, FAILURE TO COMPLY WILL VOID WARRANTY. HOSES ARE PERMANENTLY ISIZED TO THE BODY.

ELEMENTI

Page 2 of 4

Ion/Neo bath Column W/Hand Piece

EXPLODED VIEW



	1
	2
	1
	1
etal/Black/Brushed Brass)	1
	1
	3
	1
Metal/Black/Brushed Brass)	1
	1
etal/Black/Brushed Brass)	1
/Black/Brushed Brass)	1
Metal/Black/Brushed Brass)	1
I/Black/Brushed Brass)	1
Metal/Black/Brushed Brass)	1
	1
	1
	1
in Metal/Black/Brushed Brass	2
Metal/Black/Brushed Brass)	1
I/Black/Brushed Brass)	1
	1
	1
	6
tal/Black/Brushed Brass)	1
	1
	1
	1
	2
Metal/Black/Brushed Brass)	1
	2
	2
	2
	1
	1
I/Black/Brushed Brass)	1
	1
	1
seed (Olask (Osseka d Osses)	1
	k/Brushed Brass)

44285.02, 44285.29, 44285.13, 44285.04, 44285.07/170003, 170003GM,170003PH,170003SP,170003SG

44285.02, 44285.29, 44285.13, 44285.04, 44285.07/170003, 170003GM.170003PH.170003SP.170003SG 44285.02, 44285.29, 44285.13, 44285.04, 44285.04, 44285.07/170003, 170003GM.170003PH.170003SP.170003SG

44285.02, 44285.29, 44285.13, 44285.04, 44285.07/170003, 170003GM.170003PH.170003SP.170003SG